

- (PP) Corrugated Single Wall Pipe and Double Wall Pipe” for pipe size 12-30 inch.
- ASTM F2764² – “Standard Specification for 30 to 60 in. [750 to 1500 mm] Polypropylene (PP) Triple Wall Pipe and Fittings for Non-pressure Sanitary Sewer Applications” for pipe size 30 to 60 inch.

Corrugated polypropylene piping and fittings shall be listed and labeled by an approved agency accordance with section AC 28-113.2.3 and comply with conditions of this bulletin.

Uses: Corrugated polypropylene piping and fittings may be used in connection with storm sewer piping when used outside of the foundation wall of the building and not connecting to any piping system from the interior of the buildings.

Conditions of Acceptance: Corrugated polypropylene piping and fittings shall be designed and installed in accordance with the 2008 NYC Construction Codes and other applicable provisions including but not limited the following:

A. Design

1. Corrugated polypropylene piping and fittings shall be specified in accordance with the manufacturer’s recommendation and the conditions of the listing.
2. Corrugated polypropylene piping and fittings shall be a minimum of 12 inches or larger.

B. Installation Requirements

1. Installation requirements shall be in accordance with the manufacturer’s instructions, the applicable listing, and the conditions of this bulletin.
2. Installation shall be performed by a licensed master plumber.
3. Pipe and fittings shall be of the same material.
4. Corrugated polypropylene piping and fittings shall be labeled as per section AC-113.4. All shipment and deliveries of materials shall be accompanied by a label certifying the material shipped or delivered are equivalent to those tested and approved.
5. Pursuant to section BC 1704.20, the installation of corrugated polypropylene piping and fittings shall be subject to special inspection requirement of Chapter 17 of the Building Code and 1RCNY section 101-06.

C. Maintenance

1. Maintenance shall comply with all applicable requirements of 2008 NYC Construction Codes and the Rules of the City of New York.
2. Maintenance shall comply with the manufacturer’s instruction and the applicable listing.

- Referenced Standards:**
1. ASTM F 2736 -10¹ – “Standard Specification for 6 to 30 in. [152 to 762 mm] Polypropylene (PP) Corrugated Single Wall Pipe and Double Wall Pipe” for pipe size 12-30 inch.
 2. ASTM F2764-10² - “Standard Specification for 30 to 60 in. [750 to 1500 mm] Polypropylene (PP) Triple Wall Pipe and Fittings for Non-pressure Sanitary Sewer Applications” for pipe size 30 to 60 inch.