

**CITY OF NEW YORK  
DEPARTMENT OF BUILDINGS**

Pursuant to Administrative Code Section 27-131, the following equipment or material has been found acceptable for use in accordance with the Report of the Material and Equipment Acceptance (MEA) Division.

Patricia J. Lancaster, A.I.A., Commissioner  
MEA 149-02-E

Report Materials and Equipment Acceptance Division

Manufacturer – QBD Modular System Inc., 31 Bramsteele Road, Brampton, Ontario  
L6W 3K6

Trade Name – QBD.

Product – Heated display cases.

Pertinent Code Section(s) – 27-777(d), 27-787, 27-792.

Prescribed Tests – RS 14-6 (UL 197).

Laboratory - Intertek Testing Services.

Test Report – No. 273-1052-96-01, dated January 4, 1996.

Description – These units are heated display cases. Units could be made as floor mounted or counter top unit. Each unit consists of a self-contained heated system and visible food zone. Units are power connected.

Approved Models:

MODEL	* ** SYSTEM	*** MAX. BRANCH CCT. AMPS	MAX. WATTS	VOLTAGE
CAHT-XXXX	1,3,8	20	2970	120/240
CAHTIC-XX-XXXX	1,3,8	20	2970	120/240
CAHTOC-XX-XXXX	1,3,8	20	2970	120/240
CAPCH-XX-XXXX	1,8	15	2220	120/240
CASU-XX-XXXX	1,3,4,5,6,8	20	3840	120/240
CASUIC-XX-XXXX-H	1,3,4,5,6,8	20	3840	120/240
CASUOC-XX-XXXX-H	1,3,4,5,6,8	20	3840	120/240
CAUU-XX-XXXX-H	1,2,3,4,5,6,8	20	3840	120/240
CAUUC-XX-XX-H	1,2,3,4,5,6,8	20	3840	120/240
CAUUOC-XX-XX-H	1,2,3,4,5,6,8	20	3840	120/240
CLDH-XXXX	1,3,4,8	20	3840	120/240

MODEL	* ** SYSTEM	*** MAX. BRANCH CCT. AMPS	MAX. WATTS	VOLT
CLDIC-XX-H	1,3,4,8	20	3840	120
CLDIC-XX-HST	1,3,4,8	20	3840	120
CLDOC-XX-H	1,3,4,8	20	3840	120
CLDOC-XX-HST	1,3,4,8	20	3840	120
CLP-XXXX-H	1,3,4,8	20	3840	120/2
CLP-XXXX-HD	1,3,4,8	20	3840	120/2
CLPIC-XX-H	1,3,4,8	20	3840	120/2
CLPOC-XX-H	1,3,4,8	20	3840	120/2
CTH-XXXX	1,3,4,8	20	3840	120/2
CTHM-XXXX	1,3,4,8	20	3840	120/2
CTSU-XXXX	1,3,4,5,6,8	20	3840	120/2
CTTU/PcPc-H-XXXX	1,3,8	20	2970	120/2
CTTU-H-XXXX	1,3,8	20	2970	120/2
DSC-XXXX-H	1,2,3,4,5,6,8	20	3840	120/2
HC-XX	7	15	1320	120/2
SZFM-XX-IC-H	1	15	2220	120/2
SZFM-XX-OC-H	1	15	2220	120/2
SZFM-XXXX-H	1	15	2220	120/24
SZPW-XXXX	1,3,5,6,8	20	3840	120/24
SZTM-XX-IC-H	1	15	2220	120/24
SZTM-XX-OC-H	1	15	2220	120/24
SZTM-XXXX-H	1	15	2220	120/24

NOTES: The "X" in the above models are replaced by numbers representing c. length and height

\* System "number" refer to individual system

\*\* One or any combination of the systems may be used within each r

\*\*\* Maximum nameplate ratings not to exceed 80% of (Branch Amp.) Branch Circuit ampacity

Recommendation - That the above electrical heated display cases, be accepted, under the following conditions:

1. Units shall be installed in accordance with manufacturer's instructions and New York City Electrical Building and Fire Code requirements.
2. Adequate supply of fresh air shall be provided into room or space enclosing equipment for ventilation requirements.
3. The installation shall not interfere with accessibility for operation and servicing.
4. All shipments and deliveries of such equipment shall be provided with a metal tag, suitably placed, certifying that the equipment shipped or delivered is equivalent to that tested and acceptable for use, as provided for in Section 27-131 of the Building Code.
5. Approval of all electrical equipment, apparatus, materials and devices shall be obtained from the Bureau of Electrical Control before installation.

Final Acceptance 6/20/07

Examined by Shyam M. Prasad