

NYC Department of Buildings 280 Broadway, New York, NY 10007 Patricia Lancaster, FAIA, Commissioner (212) 566-5000, TTY: (212) 566-4769

Pursuant to Administrative Code Section 27-131, the following equipment or material has been found acceptable for use subject to the terms and conditions contained herein.

MEA 322-07-E

Manufacturer:	Spinnaker Industries Inc., 27 Leading Road, Etobicoke, Ontario M9V 4B7 CANADA	
Trade Name(s):	Spinnaker	
Product:	Water-cooled air conditioners and heat pumps	
Pertinent Code Section(s):	27-770, 27-777	
Prescribed Test(s):	RS 13-6 (ANSI B9.1), RS 13-11 (UL 1995) RS 14-6 (ANSI Z21.47)	
Laboratory:	Intertek Testing Services Ltd. (ITS)	
Test Report(s):	ITS Report No. 3125143COL-005 dated July 2007.	

Description: Heat pump units designed for indoor installation. R-22 refrigerant is used for the system. Unit is comprised of hermetically sealed condenser, air-cooled condenser with fan, and electrically operated reversing valve and safety controls. Units, with model numbers, cooling and heating capacities, are listed below:

Model No.	Mfr.'s Specified Cooling Capacity (Tons)	Mfr.'s Specified Heating Capacity Range (Btu/hr)
SW(H, V, HP, VP)-09	0.75	9,000
SW(H, V, HP, VP)-012	1.0	12,000
SW(H, V, HP, VP)-018	1.5	18,000
SW(H, V, HP, VP)-024	2.0	24,000
SW(H, V, HP, VP)-030	2.5	30,000
SW(H, V, HP, VP)-036	3.0	36,000
SW(H, V, HP, VP)-048	4.0	48,000
SW(H, V, HP, VP)-060	5.0	60,000

31,

Terms and Conditions: The above-described units are accepted under the following conditions:

- 1. Units shall be installed indoor only.
- 2. Units shall use only Refrigerant R-22.
- 3. If utilized for residence heating, the circulatory air system shall have (a) one register or grille without closeable shutters and the duct leading thereto shall be without a damper, or (b) dampers and shutters within the system that shall be constructed or controlled so as to prevent closure beyond 80 percent of the gross duct area at all times.
- 4. Approval of all electrical equipment, apparatus, materials and devices shall be obtained from the Department's Electrical Advisory Board before installation.
- 5. Units shall be used in compliance with the Energy Conservation Construction Code of New York State.
- 6. All shipments and deliveries of such equipment shall be provided with a metal tag, suitably placed, certifying that the equipment shipped or delivered is equivalent to that tested and acceptable for use, as provided in Section 27-131 of the New York City Building Code.

Final Acceptance <u>11/8/67</u> Examined By <u>Super</u>