

**EXISTING AVERAGE:** 

PROPOSED HOURLY PEAK:

#### NEW YORK CITY DEPARTMENT OF ENVIRONMENTAL PROTECTION BUREAU OF WASTEWATER TREATMENT

FOR OFFICIAL USE ONLY C-

## Wastewater Quality Control Application for Discharges Over 10,000 Gallons Per Day

PLEASE PRINT OR TYPE. APPLICANT MUST COMPLETE BOTH PAGES OF THIS FORM. INCORRECT OR INCOMPLETE APPLICATIONS WILL NOT BE REVIEWED. WRITE N/A IF NOT APPLICABLE. PLEASE RETURN COMPLETED FORM TO:

New York City Department of Environmental Protection Bureau of Wastewater Treatment Division of Pollution Prevention and Monitoring Industrial Resource Management and Permitting Section Wastewater Resource Management Unit 96-05 Horace Harding Expressway, 4th Floor Corona, NY 11368

1. LOCATION	TAX BLOCK	#			LOT#:	
PROJECT NAME:			BOROUGH:			
HOUSE#:	STREET NA	ZIP:				
IS THIS A DEP PROJECT	?[]YES [	]NO I	S THIS PROJECT I	DEP FUNDED? [	1 YES	[ ]NO
		<u> </u>			1	
2. APPLICANT						
LAST NAME:		FIRST NAME:				
LEGAL BUSINESS NAME						
ADDRESS:		CITY: STATE:			ZIP:	
CONTACT PERSON:				TELEPHONE: (	)	
					· /	
3. OWNER						
TYPE OF OWNERSHIP: [		L [ ]CORPORAT	TION    PARTNE	RSHIP I IGO	VERNMENT	•
	OTHER:		i ji / ii / ii			
LAST NAME:	<u>, · · · </u>	FIRST NAM	<u>л</u> Е:		M.I.:	
LEGAL BUSINESS NAME	/AGENCY:	1		TELEP	HONE: ( )	
ADDRESS:	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	(	CITY:	STATE:	ZIP:	
4. PROJECT USE						
[ ]RESIDENTIAL			NUMBER OF D	WELLING UNITS:		
[ ]COMMERCIAL TYPE:	GROSS FLOOR AREA:					
[ ]INDUSTRIAL TYPE:			GROSS FLOOR		SQ. FT SQ. FT	
[ ]OTHER, EXPLAIN:						<u>-</u>
5. LOCATION						
OBTAIN FROM BOROUG	H OFFICE AN	D INDICATE THE C	ORRECT STREET	LINES FROM TH	E CITY PLAN	N;THE
PLOT TO BE BUILT UPON	N IN RELATIO	N TO THE STREET	LINES AND THE P	ORTION OF THE	LOT TO BE	•
OCCUPIED BY THE BUIL	DING; THE H	DUSE NUMBERS A	ND THE BLOCK AN	ID LOT NUMBER	S.	
BLOCK:		LOT(S):		HOUSE NO(S):		
DIAGRAM (SHOW ARROV	W INDICATING	G NORTH)				
6. WASTEWATER & SEW	/AGE					

GALLONS/DAY

IF NO SEWERS AVAILABLE, INDICATE THE METHOD OF DISPOSAL OF WASTEWATER & SEWAGE:

GALLONS/HR

GALLONS/DAY

PROPOSED AVERAGE:

7. INDUSTRIAL/COMMERCIAL/MAN	NUFACTURING ONLY					
TYPE OF ESTABLISHMENT:		FLOOR AREA:	SQ. FT.			
WORK AREA:	SQ. FT.	STORAGE AREA:	SQ. FT.			
[ ] NEW SEWER CONNECTION AT						
[ ] EXISTING SEWER CONNECTION						
CONNECTION TO: [ ] SANITARY	[ ] COMBINED [ ]	STORM []OTHER:				
LIST ALL CHEMICALS OR HAZARD	OUS WASTES, IF ANY:					
MSDS ATTACHED? [ ] YES [	] NO					
8. DEWATERING/SPECIAL DISCHA	RGES   For disch	narges over 10,000 gallons per day (g	<i>[pd]</i>			
[ ] GROUNDWATER		[ ] WASTEWATER				
DISCHARGE FLOW RATE:	GPD DURAT	TION: DAYSOR	ONE YEAR			
[ ]GRAVITY	PUMP	EINDICATE NUMBER OF DAYS IF LESS THAN PUMP CAPACITY:	GPM			
DISCHARGE TO (NAME OF WASTE	<u> </u>		GFIVI			
DISCHARGE TO (NAME OF WASTE DISCHARGE SEWER SIZE:	IN. [ ] SANITARY	· · · · · · · · · · · · · · · · · · ·	STORM			
MSDS OF CHEMICALS USED ATTA		T TOMBINED TELE	O I OINIVI			
NYS LABORATORY ANALYTICAL R		<u> </u>				
NYSDEC PERMIT:	<u>ESULIS:   JATTACHE</u>   JATTACHE	• -				
NYSDEC PERIIIT.	[ ]ATTACHE	ED [ ]NOT AVAILABLE				
9. PRETREATMENT EQUIPMENT						
GREASE INTERCEPTOR	NO. OF UNIT:	SIZE/RATE:				
[ ]OIL/WATER SEPARATOR	NO. OF UNIT:	SIZE/RATE:				
[ ] CARBON UNIT	NO. OF UNIT:	SIZE/RATE:				
[ ] AIR STRIPPER	NO. OF UNIT:	SIZE/RATE:				
[ ] SETTLING TANK/BASIN	NO. OF UNIT:	SIZE/RATE:				
[ ]pH NEUTRALIZATION	NO. OF UNIT:	SIZE/RATE:				
WIRE BASKET	NO. OF UNIT:		SIZE/RATE:			
PLASTER TRAP	NO. OF UNIT:		SIZE/RATE:			
[ ] AMALGAM SEPARATOR	NO. OF UNIT:	SIZE/RATE:				
[ ] OTHER, EXPLAIN:	INO. OF UNIT.	JSIZE/RATE.				
[ ]OTTEK, EXPERIN.						
MANUFACTURER:		SERIAL NUMBER:				
MEA/BSA NUMBER:		REAGENT(S):				
		GROSS FLOOR AREA:	SQ FT.			
10. PROJECT DESCRIPTION/HISTO	nRV·					
TOTAL RESIDENCE TO THE PROPERTY OF THE PROPERT	21(1)					
11. STATEMENTS AND SIGNATUR	ES:					
OWNER'S NAME:	OWNER'S SIG	NATURE:	DATE:			
APPLICANT'S NAME:	APPLICANT'S	SIGNATURE:	DATE:			
NAME OF NYS PROFESSIONAL EN						
SEAL & SIGNATURE (NYS P.E. OR		AVE PREPARED OR SUPERVISED T				
		THE PLANS, SPECIFICATIONS				
		CUMENTS HEREWITH SUBMITTE				
		ST OF MY KNOWLEDGE AND BEI				
		D WORK SHOWN THEREIN CON				
		OVISIONS OF ALL NEW YORK (				
		DES AND OTHER APPLICABL GULATIONS. I AM AWARE TH				
		GULATIONS. I AM AWARE TH BNIFICANT PENALTIES FOR SUE				
SIGNATURE OF NYS P.E. OR R.A.: INFORMATION, INCLUDING THE POSSIBLITILITY OF						
DATE: FINE AND/OR IMPRISONMENT.						
		- <del> </del>				

# NEW YORK CITY DEPARTMENT OF ENVIRONMENTAL PROTECTION BUREAU OF WASTEWATER TREATMENT (BWT) INDUSTRIAL RESOURCE MANAGEMENT AND PERMITTING SECTION

### PROCEDURE FOR OBTAINING BWT LETTER OF APPROVAL FOR GROUNDWATER DISCHARGE OVER 10,000 GALLONS PER DAY TO SANITARY OR COMBINED SEWER

#### Applicant must submit:

- 1. One cover letter describing the project in details.
- 2. One complete Wastewater Quality Control (WQC) application.\*
- 3. One Site Plan (to scale)\*. The site plan must indicate, at a minimum:
  - Location, type (sanitary or combined), and size of the public sewer.
  - Existing and proposed sewer connections from the project site to the public sewer line (indicate whether the connecting pipe is above or below ground level).
  - Adjacent streets around the project site.
  - Location of equipment: pumps, pipes, pretreatment equipment, etc.
  - Location(s) of point(s) of discharge (POD).
  - Location and description of sampling point location(s).
  - Pump capacity (capacities) in gallons per minute (gpm).
  - Properly <u>sized</u> and <u>approved</u> pretreatment systems. Manufacturer specifications and engineering must also be submitted.
  - A detailed flow/layout diagram of the different types of pretreatment equipment used.
  - Clearly drawn property lines of the project site.
- 4. An analytical report of the groundwater to be discharged. Samples must be taken downstream from pretreatment equipment if such exists, and be representative of nature of proposed groundwater discharge. All laboratory analyses must be conducted by a New York State Department of Health certified wastewater laboratory for the parameters listed in Table A. The results must be certified by the laboratory and submitted on the laboratory's letterhead. For each sample, the laboratory report must indicate, at a minimum: the date of sampling, time sample was taken, sample location, chain of custody, sampling preservation procedures, analytical techniques used, date of analysis, units of measurement, and the laboratory's sample identification. Where the analytical result reported is below the method detection level, the laboratory report must also indicate the method detection level.

The project name referenced on the analytical report must be identified exactly as it is in the WQC application.

- **5.** If the proposed discharge is **10,000 gallons per day or less**, a Self-Certification Form must be submitted to NYCDEP Bureau of Customer Services, Borough Operations. Any inquiry should be forwarded to dewatering@dep.nyc.gov.
- **6.** If the proposed discharge exceeds 10,000 gallons per day, additional approval must be obtained from the NYCDEP Bureau of Water and Sewer Operations, Chief of Permitting and Compliance. The contact person is Mr. Suresh Kumar, Engineer-In-Charge, and can be reached at (718) 595-5205.
- 7. Prior to commencement of discharge, the permittee must obtain a Dewatering Permit from respective Borough Office contingent to presenting the Letter(s) of Approval and upfront payment of sewer charges, if required.
- **8.** The Letter of Approval is contingent upon the permittee's compliance with any federal, state, or local requirements applicable to the permitted activity.
- **9.** The application must be signed by:
  - i. The officer or director if owner/applicant is a corporation; or
  - ii. The partner, general and limited, if owner/applicant is a partnership; or
  - iii. The officer, director, partner, or owner if owner/applicant is a limited liability company; or
  - iv. The owner, if owner/applicant is a sole proprietorship
- 10. All inquiries should be directed to the attention of Sean H. Hulbert, P.E. at (718) 595-4715.
  - \* This document must include <u>original</u> stamp and signature of a New York State (NYS) Professional Engineer (P.E.) or Registered Architect (R.A.).

Parameter <sup>1</sup>	Daily Limit	Units	Sample Type	Monthly Limit
Non-polar material <sup>2</sup>	50	mg/l	Instantaneous	
pH	5-12	SUs	Instantaneous	
Temperature	< 150	Degree F	Instantaneous	
Flash Point	> 140	Degree F	Instantaneous	
Cadmium	2	mg/l	Instantaneous	
	0.69	mg/l	Composite	
Chromium (VI)	5	mg/l	Instantaneous	
Copper	5	mg/l	Instantaneous	
Lead	2	mg/l	Instantaneous	
Mercury	0.05	mg/l	Instantaneous	
Nickel	3	mg/l	Instantaneous	
Zinc	5	mg/l	Instantaneous	
Benzene	134	ppb	Instantaneous	57
Carbontetrachloride			Composite	
Chloroform			Composite	
1,4 Dichlorobenzene			Composite	
Ethylbenzene	380	ppb	Instantaneous	142
MTBE (Methyl-Tert- Butyl-Ether)	50	ppb	Instantaneous	
Naphthalene	47	ppb	Composite	19
Phenol			Composite	
Tetrachloroethylene (Perc)	20	ppb	Instantaneous	
Toluene	74	ppb	Instantaneous	28
1,2,4 Trichlorobenzene			Composite	
1,1,1 Trichloroethane			Composite	
Xylenes (Total)	74	ppb	Instantaneous	28
PCBs (Total) <sup>3</sup>	1	ppb	Composite	
Total Suspended Solids (TSS)	350	mg/l	Instantaneous	
CBOD			Composite	
Chloride			Instantaneous	
Total Nitrogen <sup>4</sup>			Composite	
Total Solids			Instantaneous	
Other				

TABLE A

LIMITATIONS FOR EFFLUENT TO **SANITARY OR COMBINED** SEWERS

- All handling and preservation of collected samples and laboratory analyses of samples shall be performed in accordance with 40 C.F.R. pt. 136. If 40 C.F.R. pt. 136 does not cover the pollutant in question, the handling, preservation, and analysis must be performed in accordance with the latest edition of "Standard Methods for the Examination of Water and Wastewater." All analyses shall be performed using a detection level less than the lowest applicable regulatory discharge limit. If a parameter does not have a limit, then the detection level is defined as the method detection limit (MDL) and limit of quantitation (LOQ) required by the analytical method that is used to analyze the parameter. If the method does not contain an MDL or LOQ, the lab must use an approved method that does contain an MDL or LOQ. If none of the approved methods contain an MDL or LOQ for that parameter then the lab must develop its own LOQ, and report it with the analytical results.
- Non-polar material means that portion of the oil and grease that is not eliminated from a solution containing N-Hexane, or any other extractant the EPA shall prescribe, by silica gel or any other means of adsorption the EPA shall prescribe.
- Analysis for PCBs is required if duration of a discharge is greater than 10 days. Analysis for PCBs must be done by EPA method 608 with MDL=<65 ppt. PCBs (total) is the sum of PCB-1242 (Arochlor 1242), PCB-1254 (Arochlor 1254), PCB-1221 (Arochlor 1221), PCB-1232 (Arochlor 1232), PCB-1248 (Arochlor 1248), PCB-1260 (Arochlor 1260) and PCB-1016 (Arochlor 1016).
- 4 Total Nitrogen = Total Kjeldahl Nitrogen (TKN) + Nitrite (NO<sub>2</sub>) + Nitrate (NO<sub>3</sub>).