

A photograph of the Brooklyn Bridge Promenade. The image shows the suspension cables and stone towers of the bridge, with a clear blue sky in the background. In the foreground, several people are walking along the wooden boardwalk. A semi-transparent dark grey banner is overlaid across the middle of the image, containing the title and subtitle text.

BROOKLYN BRIDGE PROMENADE

New York City Department of Transportation

August 2016



OUTLINE

- I. Brooklyn Bridge – Times Square in the Sky**
- II. Lives of the Brooklyn Bridge**
- III. Project Overview**
- IV. Promenade Typologies & Issues**
- V. Deck to Girder Relationship**
- VI. Initial Improvement Concepts**
- VII. Process/Next Steps**



BROOKLYN BRIDGE


Times Square in the Sky




I. BROOKLYN BRIDGE – TIMES SQUARE IN THE SKY



The Brooklyn Bridge is more than a way to get from point A to B. It is a destination.



- Picture taking
- Sitting
- Talking
- Communicating
- Performing
- Selling/Buying



I. BROOKLYN BRIDGE – TIMES SQUARE IN THE SKY

No formal system for providing services to Bridge visitors



TIMES SQUARE IN THE SKY

Average Peak Hour Volumes

Spring 2008 vs. Spring 2015

- Pedestrian volumes have increased 20% in the PM and 275% on the weekend from May 2008 to May 2015
- Bicycle volumes have increased 66% in the AM and 93% in the PM from May 2008 to May 2015


Typical Weekday Volumes

- 100,000 Motor vehicles
- 10,000 Pedestrians
- 3,500 Cyclists


DOT Bi-Annual Pedestrian Counts (Spring)

AM counts averaged: 7-9AM, PM counts averaged: 4-7PM, Weekend counts averaged: 12-2PM

Pedestrian Volumes




Bicycle Volumes




LIVES OF THE BROOKLYN BRIDGE



- **May 24th, 1883** - Opened for horse-drawn and rail traffic with elevated promenade for pedestrians and cyclists
- **1898** - Roadway configured to allow trolley and carriages
- **1944** - Manhattan and Brooklyn terminals torn down, elevated trains removed
- **1950** - Bridge closed for construction - Trolley tracks removed and traffic restricted to passenger cars. There are currently six lanes of vehicular traffic
- **1980s** – Ramp to Adams/Tillary St added; Stairs to Towers Removed



1883



SECTION OF BRIDGE, SHOWING FOOT, RAIL, AND CARRIAGE WAYS.

1982 STAIRS TO TOWERS REMOVED

1983 RAMP/CATTLE CHUTE TO TILLARY STREET CONSTRUCTED

Brooklyn Bridge: Reconstruction of the promenade began in 1982. Controversy over design resulted from conflicting user demands. Handicapped and bicycle groups were in favor of replacing all four stairways with ramps. Preservationists contended that the existing steps were an integral part of the promenade and must remain. After a public hearing in May, 1982, the Landmarks Preservation Commission approved the removal of the stairs and construction of a fully ramped promenade. Reconstruction of the promenade between the two towers took place between August and December, 1982. A temporary walkway was installed eight feet above the existing promenade to allow pedestrians and bicycles to cross the Bridge during reconstruction. After the Brooklyn Bridge centennial celebration in May, 1983, a new 10' to 12' wide bikepath will be constructed at the Brooklyn approach in conjunction with promenade reconstruction between the towers and land (See Photo 12). This will eliminate the need to carry bicycles up or down a 3-level staircase of over 30 steps.





Photo 12. Brooklyn Bridge: projected Bike Path leading to Tillary Street



PROJECT OVERVIEW



BROOKLYN BRIDGE PROMENADE

Goals

- Relieve overcrowding of existing promenade
- Enhance the visitor experience of the iconic and historic Brooklyn Bridge promenade
- Greatly reduce conflicts between and improve safety of cyclists, pedestrians, and visitors on the promenade



PROCESS

1. Initial Assessment

DOT has performed an initial assessment of the Brooklyn Bridge existing conditions, issues, and opportunities

2. Consultant Study Tasks

Aug '16 -- Feb '17, \$370k

- a) Structural Analysis
- b) Conceptual Design Development
- c) Historical Preservation Implication Study
- d) Conceptual Cost Estimate

If feasible


3. Design & Construction

- a) Potentially via upcoming/planned bridge capital contract



PROMENADE TYPOLOGIES & ISSUES


IV




- 1 Concrete Approaches - 2365 feet: 35%
- 2 Wood Deck Approaches - 750 feet: 11%
- 3 Wood Deck with Cables - 1,510 feet: 23%
- 4 Tower Ramps - 540 feet: 8%
- 5 Towers - 109 feet: 2%
- 6 Crown - 355 feet: 5%
- 7 Trunk Cable Bases - 114 feet, 2%
- 8 Brooklyn Curve - 910 feet: 14%
- Extents of Girders

The width of the bike/pedestrian promenade changes frequently.
The majority of the pathway varies from 10' to 17'


1. CONCRETE APPROACHES




Widest area, but pedestrians coming up from stairs must cross over bike lane to enter promenade




1. CONCRETE APPROACHES



Staircase creates pinch point. Bikes traveling at high downhill speed do not have space to pass bikes entering the bridge



CONCRETE/ WOOD DECK TRANSITION




Benches narrow pedestrian space

Wooden promenade with adjacent girders

Concrete pathway



2. WOOD DECK APPROACHES




Width of 16' is generally acceptable for a shared use path.

Stopping for picture taking creates pinch points and conflicts with walking and cycling




3. WOOD DECK WITH CABLES



Cyclists shy a foot away from cables, further reducing effective width

Cable supports connect inside of fence narrowing effective width of pathway



4. TOWER RAMPS




Approaching tower, fence moves from outside of cables to inside, narrowing path further




5. TOWERS



Pedestrians cross bike lanes for photos and views at Tower expansion




6. CROWN



Approaching the Manhattan tower at the crown is the most popular section for stopping & taking photos



7. TRUNK CABLE BASES




Narrowest point on bridge is at trunk cable bases where the path is 10'

Iconic view for photos at narrowest point on bridge



8. BROOKLYN CURVE





Narrow path,
excess space on
north side of
fence to
accommodate
staircase



DECK TO GIRDER RELATIONSHIP

V

TYPICAL BRIDGE CROSS-SECTION





Height relationship
between promenade
and girders

The majority of the
wood deck is 4' below
girders except at the
towers and tower
ramps



RAMP UP TO GIRDER HEIGHT





Pathway ramps up to girder height approaching towers

INITIAL IMPROVEMENT CONCEPTS

VI

OPPORTUNITY FOR ADDITIONAL SPACE



Pathway expands
on top of girders
around towers


Potential pedestrian
space



Potential expansion over girders

Rendering shows new
space between towers
only, concepts beyond
towers will be
explored


BETWEEN TOWERS CONCEPT




6 Crown

3 Wood Deck with Cables

- Build pedestrian decks over roadway girders
Option 1: Dual Deck or Option 2: Single Deck
- Midpoint ramps and stop controlled crossings allowing pedestrian access across bike path.
- Support stopping/resting activities, consider light touch concessions and Citibike station




TOWER CONCEPT



5 Towers

- Add stop controlled crosswalks to existing markings to calm cyclists and allow pedestrian access.
- Support stopping/resting activities, consider light touch concessions and Citibike stations




TOWER APPROACH CONCEPT

2 Wood Deck Approaches

3 Wood Deck with Cables

4 Tower Ramps


- Build pedestrian deck over roadway girders or length of cables



EXISTING




CONCEPT



If needed to limit additional weight new pedestrian deck can be forgone for **Wood Deck Approaches** that are 16' wide with no wires. Consider shifting centerline to add space for pedestrians



CONCRETE APPROACH CONCEPT





1 Concrete Approaches

Short Range:


- Reallocate existing even split between bikes and pedestrians to 10' for pedestrians and 7' for bikes.
- Add seasonal fence to reduce conflicts

Long Range:

- Build out of elevated cantilevered walkways



STAIR PINCH POINT CONCEPT




7 Stair Pinch Points

- **Brooklyn Stairs** - Add stop controls and crossings to manage speed/conflicts.
- **Manhattan Stairs** - Explore feasibility of closing & covering stairway.




BROOKLYN CURVE CONCEPT



8 Brooklyn Curve

- Room to reallocate roadway space and/or unused promenade space to widen pedestrian/bicyclist path



PROCESS/NEXT STEPS

VI

PROCESS / NEXT STEPS

1. Initial Assessment

DOT has performed an initial assessment of the Brooklyn Bridge existing conditions, issues, and opportunities

2. Consultant Study Tasks

Aug '16 -- Feb '17, \$370k

- a) Structural Analysis
- b) Conceptual Design Development
- c) Historical Preservation Implication Study
- d) Conceptual Cost Estimate

If feasible

3. Design & Construction

- a) Potentially via upcoming/planned bridge capital contract





NYC DOT



NYC DOT



nyc_dot



NYC DOT